

THIS IS TO SIGNIFY THAT THE FOLLOWING PRODUCTS FOR RESIDENTIAL CONSTRUCTION

**KOPPERS NATUREWOOD® ACQ TREATED WOOD** 

MANUFACTURED BY

**KOPPERS PERFORMANCE CHEMICALS** 

HAVE BEEN CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO THE ICC 700 NATIONAL GREEN BUILDING STANDARD AS DETAILED IN NGBS GREEN CERTIFIED PRODUCT REPORT #NGBSGCP-000076.

Thomas M. Kenney, P.E. – VP Research & Engineering

April 26, 2013

Approval Date

July 31, 2021 Expiration Date

CERTIFICATE #000076

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certified Product Report #NGBSGCP-000076

Products: Koppers NatureWood® ACQ Treated Wood

Manufacturer: Koppers Performance Chemicals

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

| 2012 NATIONAL GREEN BUILDING STANDARD |   |                            |  |  |  |  |
|---------------------------------------|---|----------------------------|--|--|--|--|
| PRACTICE #                            | PRACTICE DESCRIPTION  | POTENTIAL POINTS AVAILABLE | Additional Conditions of Use to<br>Award Points  |  |  |  |
| 2012 NGBS<br>602.1.6                  | Termite-resistant materials are used in portions of the building. | 2-6                        | To earn 2 points, product is used in conjunction with other termite resistant materials for the first 2' of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites. |  |  |  |

| 2015 NATIONAL GREEN BUILDING STANDARD |   |                            |  |  |  |
|---------------------------------------|---|----------------------------|--|--|--|
| PRACTICE #                            | Practice Description  | POTENTIAL POINTS AVAILABLE | Additional Conditions of Use to<br>Award Points  |  |  |
| 2015 NGBS<br>602.1.6                  | Termite-resistant materials are used in portions of the building. | 2-6                        | To earn 2 points, product is used in conjunction with other termite resistant materials for the first 2' of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites. |  |  |

## NGBS Green Certified Product Report #NGBSGCP-000076 Page 2 of 2

| 2020 NATIONAL GREEN BUILDING STANDARD |   |                            |  |  |  |
|---------------------------------------|---|----------------------------|--|--|--|
| Practice #                            | Practice Description  | POTENTIAL POINTS AVAILABLE | Additional Conditions of Use to<br>Award Points  |  |  |
| 2020 NGBS<br>602.1.6                  | Termite-resistant materials are used in portions of the building. | 2-6                        | To earn 2 points, product is used in conjunction with other termite resistant materials for the first 2' of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites. |  |  |